

## CERTIFICATE OF ANALYSIS

**Product Name:** EPDM Rubber Sponje / Goma Esponja EPDM

**Material Profile:**

**Color:** Black / Negro

**Technical Details:**

1. Hardness: 18 +/- 7 Shore A
2. Tensile Strength (Mpa): 0.7 a 1 Mpa
3. Elongation at Break (%): 570 +/- 50%
4. Temperature Range: -10° a 60° (C°)

THICKNESS	WIDTH (MM)	COLORS
3 MM	15 – 20 – 25 – 30 – 40 – 50	BLACK
5 MM	10 – 15 – 20 – 25 – 30 – 40 – 50	BLACK
6 MM	15 – 20 – 25 – 30 – 40 – 80 – 100	BLACK
8 MM	10 – 20 – 100	BLACK
10 MM	10 – 15 – 20 – 25 – 30 – 40 – 50 – 70 – 80 – 100 – 200	BLACK
12 MM	15 – 20 – 25 – 30 – 40 – 50 – 70 – 100	BLACK
15 MM	15 – 20 – 25 – 30 – 40 – 50 – 100	BLACK
20 MM	20 – 25 – 30 – 40 – 50 – 60 – 80 – 100	BLACK
25 MM	25 – 30 – 35 – 40 – 50 – 70 – 100	BLACK
30 MM	30 – 40 – 50 – 60 – 70	BLACK
35 MM	35	BLACK
40 MM	40 – 50 – 60	BLACK
50 MM	50	BLACK



## CERTIFICATE OF ANALYSIS

---

**Product Name:** EPDM Sponge Rubber High Density  
Goma Esponja de Alta Densidad EPDM

**Material Profile:**

**Color:** Black / Negro

**Technical Details:**

- 5. Hardness: 25 +/- 5 Shore A
- 6. Tensile Strength (Mpa): 0.7 a 1 Mpa
- 7. Elongation at Break (%): 570 +/- 50%
- 8. Temperature Range: -10° a 60° (C°)

---

THICKNESS	WIDTH (MM)	COLORS
12 MM	30	BLACK
15 MM	25 – 30 – 40 - 50	BLACK
20 MM	20 – 25 – 30 – 40 – 50	BLACK
25 MM	25 – 30 – 40 – 70 – 100	BLACK
30 MM	40	BLACK
40 MM	40 – 50 - 60	BLACK

